

## Model number list

Criterion water flow rate [L/h]	Air flow rate [m <sup>3</sup> /h(nor)]	Water flow rate[L/h] at following water pressure[MPa]			Spray angle	Model number of nozzle tip		Model No. of mixing body
		0.2	0.3	0.4		Flat	Full-cone	
30	4.5	24	30	36	30°	¼ KSAMM 0430	¼ KSAMD 09X6-30	¼ A18 ¼ W10
					60°	¼ KSAMM 0370	¼ KSAMD 09X6-60	
					90°	¼ KSAMM 03125	¼ KSAMD 09X6-90	
50	7.5	36	50	60	30°	¼ KSAMM 0738	¼ KSAMD 105X8-30	¼ A25 ¼ W14
					60°	¼ KSAMM 0666	¼ KSAMD 105X8-60	
					90°	¼ KSAMM 06115	¼ KSAMD 105X8-90	
70	10.5	54	70	84	30°	¼ KSAMM 1039	¼ KSAMD 13X8-30	¼ A29 ¼ W16
					60°	¼ KSAMM 0965	¼ KSAMD 13X8-60	
					90°	¼ KSAMM 09137	¼ KSAMD 13X8-90	
100	15.0	72	100	120	30°	¼ KSAMM 1848	¼ KSAMD 16X8-30	¼ A35 ¼ W19
					60°	¼ KSAMM 1483	¼ KSAMD 16X8-60	
					90°	¼ KSAMM 12119	¼ KSAMD 16X8-90	
150	22.5	120	150	180	30°	¼ KSAMM 2230	¼ KSAMD 21X8-30	¼ A42 ¼ W23
					60°	¼ KSAMM 2081	¼ KSAMD 21X8-60	
					90°	¼ KSAMM 22125	¼ KSAMD 21X8-90	
200	30	156	200	240	30°	⅜ KSAMM 2736	⅜ KSAMD 22X8-30	⅜ A48 ⅜ W27
					60°	⅜ KSAMM 2572	⅜ KSAMD 22X8-60	
					90°	⅜ KSAMM 26102	⅜ KSAMD 22X8-90	
300	45	240	300	372	30°	⅜ KSAMM 3835	⅜ KSAMD 27X8-30	⅜ A62 ⅜ W35
					60°	⅜ KSAMM 3775	⅜ KSAMD 27X8-60	
					90°	⅜ KSAMM 37108	⅜ KSAMD 27X8-90	
400	60	312	400	500	30°	⅜ KSAMM 5828	-	⅜ A71 ⅜ W40
					60°	⅜ KSAMM 5865	-	
					90°	⅜ KSAMM 54115	-	
500	75	378	500	600	30°	½ KSAMM 6929	-	½ A80 ½ W45
					60°	½ KSAMM 6965	-	
					90°	½ KSAMM 61115	-	

\*The criterion water flow rate is a value of air pressure 0.3 MPa or less, water pressure 0.3 MPa or less, and air-water volume ratio 150.